

## EFT/Burst Coupling/Decoupling Network

### EFTN 11080D



#### In Compliance with

- > IEC/EN 61000-4-4
- > GB/T 17626.4
- > IEC 61000-6-1
- > IEC 61000-6-2

#### Introduction

EFTN 11080D Manual coupling/decoupling network is meeting IEC 61000-4-4 requirements, and has the characteristics of good reliability, stable performance and convenient use. Maximum EUT load capacity: DC 1100 V, 80 A.

#### Features

- > EUT DC supply can reach MAX DC 1100 V;
- > Maximum current can reach 80 A;
- > Maximum pulse voltage can reach 4 kV;
- > Manually select the coupling decoupling path;

#### Application Areas

- |                 |                    |
|-----------------|--------------------|
| > Communication | > Information      |
| technology      |                    |
| > Telecom       | > Military         |
| > Medical       | > Aviation         |
| > Radio and TV  | > New energy power |
| > Railway       | > Electric Vehicle |

Technical Parameters	
EUT supply voltage	MAX 1100 VDC
EUT current	MAX 80 A
Burst voltage	MAX 4 kV
Coupling path	DC+, DC-, PE
Coupling switching mode	Manual
Coupling capacity	33nF
Residual pulse voltage at the injection of EUT	Less than 10% of test pulse voltage
Grounding mode	4mm banana line
Burst INPUT port	Coaxial cable
EFT INPUT mode	Single or multi-line simultaneous injection

General Parameters	
Cabinet size	4 U 450×192×610 mm
Weight	Approx.25 kg
Ambient Temperature	15 °C ~ 35 °C
Relative Humidity	45% ~ 75%
Atmospheric Pressure	86 kPa ~ 106 kPa

Standard Accessories
User manual, Fuse, Three-core power cord, Test wire, Coaxial cable, Ground wire

Optional Accessories
TFB 500: input impedance 50 Ω, output impedance 50 Ω, attenuation 500:1 ;
TFB 1000: input impedance 1000 Ω, output impedance 50 Ω, attenuation 1000:1 ;
Coaxial adapter: BNC-FFM
High voltage RF connector : SHV-BNC-JJ



## **SUZHOU 3CTEST ELECTRONIC CO., LTD.**

Add.: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

Tel: +86 (0)512 6807 7192      Fax: +86-512-68079795

Sales Email: [globalsales@3ctest.cn](mailto:globalsales@3ctest.cn)      Service Email: [service@3ctest.cn](mailto:service@3ctest.cn)

[www.3c-test.com](http://www.3c-test.com)

3ctest is always striving for product innovation and quality improvement.

Product appearance and technical specifications are subject to change without further notice.

© 3ctest