

# Coupling/Decoupling Networks for Unscreened Unsymmetrical Lines CDN AF2



## In Compliance with

- > IEC61000-4-6
- > EN 61000-4-6
- > GB/T 17626.6

## Introduction

The CDN AF2 is designed according to IEC/EN 61000-4-6, which specifies clearly on the design and performance of coupling/decoupling networks. The CDN AF2 is applicable to 1-pair unscreened unbalanced lines.

## Features

- > Applicable to signal transmission rate of 10 Mbit/s;
- > Used for 1-pair (2-line) unscreened unbalanced lines;

## Application Areas

- > Communication
- > Telecom
- > Medical
- > Broadcast
- > Railway
- > IT
- > Military
- > Avionics
- > New energy power
- > New energy vehicle

Technical Parameters	
Frequency	150 kHz ~ 80 MHz
Max. AC Voltage (L-PE)	60 V
Max. DC Voltage (L-PE)	100 V
Max. Current	0.5 A
RF Input Terminal (BNC)	<15 V
EUT Port	4mm banana
AE Port	4mm banana
Transmission Rate	10 Mbit/s
Common-mode Impedance (EUT)	
150 kHz ~ 26 MHz	150 Ω ± 20 Ω
26 MHz ~ 80 MHz	150 Ω +60 Ω / -45 Ω
Voltage Division Coefficient (RF Input-EUT)	
150 kHz ~ 80 MHz	9.5 dB ± 1 dB
Common-mode Disturbances Suppression (RF Port / AE)	
150 kHz:	>60 dB
1.5 MHz:	>60 dB
30 MHz:	>50 dB
80 MHz:	>50 dB
230 MHz	>40 dB

General Parameters	
Weight	Approx. 4 kg
Dimension	210 mm(L) x 170 mm(W) x 115 mm(H)
Enclosure Material	Aluminum
Ambient Temperature	15°C-35°C
Relative Humidity	45% - 75%
Package Case	Carton

Accessories	
CAL 100F	150 Ω to 50 Ω calibration device
CAL 150F	150 Ω calibration device
CDN ADP M4	Calibration adapter



## **SUZHOU 3CTEST ELECTRONIC CO., LTD.**

Add.: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

Tel: +86 (0)512 6807 7192      Fax: +86-512-68079795

Sales Email: [globalsales@3ctest.cn](mailto:globalsales@3ctest.cn)      Service Email: [service@3ctest.cn](mailto:service@3ctest.cn)

[www.3c-test.com](http://www.3c-test.com)