

Coupling/Decoupling Networks for USB Port lines

CDN USB

Datasheet



In Compliance with

- > IEC61000-4-6
- > EN 61000-4-6
- > GB/T17626.6

Introduction

The CDN USB is designed according to IEC/EN 61000-4-6, which specifies clearly on the design and performance of coupling/decoupling networks. The CDN USB is applicable to USB port serial lines (shielded lines).

Features

- > Maximum withstand current 1A;
- > Applicable to USB port serial lines (shielded lines);

Application Areas

- > Communication
- > Telecom
- > Medical
- > Broadcast
- > Railway
- > IT
- > Military
- > Avionics
- > New energy

Technical Parameters	
Frequency	150 kHz ~ 230 MHz
Max. AC Voltage (L-PE)	100 V
Max. DC Voltage (L-PE)	100 V
Max. Current	1 A
RF Input Terminal (BNC)	<20 V
EUT Port	USB-B
AE Port	USB-A
Common-mode Impedance (EUT)	
150 kHz ~ 26 MHz	150 Ω±20 Ω
26 MHz ~ 80 MHz	150 Ω +60 Ω /-45 Ω
Voltage Division Coefficient (RF Input-EUT)	
150 kHz ~ 80 MHz	9.5 dB±1 dB
80 MHz ~ 230 MHz	9.5 dB±2 dB
Common-mode Disturbances Suppression (RF Port / AE)	
150 kHz:	>60 dB
1.5 MHz:	>60 dB
30 MHz:	>50 dB
80 MHz:	>50 dB
230 MHz	>40 dB

General Parameters	
Weight	Approx. 4 kg
Dimension	210 mm(L) x 170 mm(W) x 115 mm(H)
Enclosure Material	Aluminum
Ambient Temperature	15°C-35°C
Relative Humidity	45% - 75%
Package Case	Carton

Accessories	
CAL 100F	150 Ω to 50 Ω calibration device
CAL 150F	150 Ω calibration device
CDN USB-A/CDN	Calibration adapter
CDN USB-B/CDN	Calibration adapter



SUZHOU 3CTEST ELECTRONIC CO., LTD.

Add.: No. 99 E'meishan Road, SND, Suzhou, Jiangsu Province, China

Tel: +86 (0)512 6807 7192 Fax: +86-512-68079795

Sales Email: globalsales@3ctest.cn Service Email: service@3ctest.cn

www.3c-test.com