

Vacuum Pumps and Air Compressors

Below is left blank intentionally.

Vacuum Pumps

VP-125

Application	For vacuum fixation of DUT, chucks, and micropositioners.
Vacuum level	-33kPa(-250mmHg)
Volume	7L/min
Inlet/Outlet	Compatible with 6mm~8mm lines, OD
Power	110V/220V ±10%
Weight	0.7kg
Dimensions	92mm*58mm*90mm(W*D*H)



VP-D16C

Application	Used with CryoPS to pump down to basic vacuum level.
Vacuum level	4×10^{-4} mbar
Volume	17m ³ /h
Inlet/Outlet	KF25
Power	110V/220V ±10%



Air Compressors

AC-45DB

Application	Compressed air source
Volume	80L/min
Pressure (max)	8bar/120psi
Container Volume	30L
Working Noise	45dB
Weight	50kg
Dimensions	600mm*430mm*650mm(W*D*H)
Power	110V/220V ±10%



AC-35DB

Application	Compressed air source
Volume	17L/min
Pressure (max)	8bar/120psi
Container Volume	4L
Working Noise	35dB
Weight	18kg
Dimensions	382mm*300mm*334mm(W*D*H)
Power	110V/220V ±10%



KeyFactor™

One of the key factors to your tests & measurements.

All specifications and designs in this catalog are subject to change without notice.

All Rights Reserved. KeyFactor Systems, Inc.

KeyFactor Systems, Inc.

www.keyfactorsystems.com

sales@keyfactorsystems.com

technical-support@keyfactorsystems.com

U.S.

Add: 8825 53 AVE Elmhurst, New York, United States.

Tel: +1(347) 994-9951

China

Add: 5th FL, Sohovark, Industrial Rd. South, SSL, Dongguan.

Tel: +86(769)2223-8503

Fax: +86(769)2223-0701